

	Standard	Result
Thickness		4.5 mm
Size		500 mm x 610 mm
Wear layer		20 mil (0.50 mm)
Surface treatment		K-Guard+ PU coating
Warranty ¹	Commercial Residential	15 Years Lifetime
Beveled Edge		No
Classification	ASTM F1700	Class III Type B
Reaction to fire	ASTM E648-06	Class 1
Smoke density	ASTM E662-06	Pass (< 450)
Flammability test	FF 1-70; Federal Approval	Pass
Slip resistance ²	ASTM D2047	Dry 0.92
Staining resistance	ASTM F925	Pass
Light fastness	ASTM F1515	Pass $\Delta E = 1.7$
Abrasion resistance	ASTM D3884	113,000 Cycles
Dimensional stability	ASTM F2199	Pass 0.0045"/lin.ft
Acoustic impact noise reduction	ASTM E2179-09 ASTM E492-09	$\Delta IIC = 16$ dB IIC = 56 dB (6" Concrete Slab w/Drop Ceiling) IIC = 71 dB (6" Concrete Slab w/Drop Ceiling + QuietChoice)
Static load	ASTM F970	1,000 psi
Flexibility	ASTM F137	Pass
Electrostatic propensity	AATCC 134-1996	Pass
Indentation - residual	ASTM F1914	< 0.003"
Adhesive		Please refer to our installation instructions.
Environmental	FloorScore® SCS-EC10.3-2014 v4.0 Environmental Product Declaration NSF / ANSI 332 ISO 14001 / ISO 9001	Indoor air quality certified; Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification) Sustainability Assessment for Resilient Floor Coverings; Silver certified product Manufactured to quality and environment management systems standards
Recycling		Suitable
Phthalate free		Yes

¹ Subject to terms. Please see our website.


² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

Call: 866-819-6825

Email: info@karndeancanada.ca

Visit: www.karndean.com



	Product Code	Size		Box Quantity	
		inches	mm	ft ²	Pieces
Stone Designs	LLT201	19.69" x 24.02"	500 x 610	32.83	10 Tiles
	LLT203	19.69" x 24.02"	500 x 610	32.83	10 Tiles
	LLT208	19.69" x 24.02"	500 x 610	32.83	10 Tiles
	LLT209	19.69" x 24.02"	500 x 610	32.83	10 Tiles
	LLT212	19.69" x 24.02"	500 x 610	32.83	10 Tiles
	LLT214	19.69" x 24.02"	500 x 610	32.83	10 Tiles
	LLT217	19.69" x 24.02"	500 x 610	32.83	10 Tiles
	LLT218	19.69" x 24.02"	500 x 610	32.83	10 Tiles